



**Warewashing
Small Glasswasher, double skin
with drain pump and detergent
dispenser-UK plug, 30r/h**

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



402168 (VGWSIGUK)

Glasswasher (small), double skin, with drain pump, rinse aid and detergent dispensers, 1 cycle, 30r/h - Uk plug

Short Form Specification

Item No. _____

Unit shall be Glasswasher type hot water rinsing for rack dimension of 400*400mm. Electrical characteristics to be 230 single phase operation with one wash cycle of 120 seconds. Rinse temperature and pressure guaranteed by built in pressure boiler. Washing performance is ensured by a powerful wash pump, revolving washing spray arms from both bottom and top. Double skinned counter-balance door. Double skin cabinet. 304 stainless steel construction to include door, frame, wash arms and rinse arms. The unit shall include drain pump, detergent and rinse aid dispenser pump and be equipped with electric cable with UK plug.

Main Features

- Built-in rinse aid dispenser with automatic initial and continuous cycle loading for perfect result while minimizing service and maintenance needs.
- Double skinned insulated wall ensures a low noise level and a reduction in heat loss from the machine.
- Built-in pressure boiler designed to raise incoming water to a guaranteed minimum temperature of 82°C for sanitizing rinse. No external boiler is required.
- Equipped with drain pump for easy and quick installation without opening the machine.
- Maximum capacity of 30 racks per hour.
- Washing system endowed with rotating washing arms from both top and bottom, high powered wash pump and large capacity wash tank guarantee professional washing.
- 120 seconds cycle.
- Simple operation control panel.
- Easy service access to main components without moving the unit.
- Solid double skinned counter-balance door with hurt-free handle fully in stainless steel.
- Deep drawn pressed wash tank with fully rounded corners, sloped towards the drain to prevent dirt build up provides fast drainage in only a few minutes. Pressed wash tank with no welded points offer a guaranteed water tight solution.

Construction

- Completely closed on the back by a cover plate.
- Internal components (arms and filter) are easy extractable.
- Unit to include detergent and rinse aid dispenser pumps.
- Equipped with single phase electrical cable and 13 amp UK plug for easy and fast installation.
- Finished in top quality stainless steel with double skinned construction to aid durability and reduce noise.
- Requires only 1 phase 230V supply.

Included Accessories

- 1 of Square basket for glasses 400x400x150mm PNC 864470


Optional Accessories

- Stainless steel tank filter PNC 864003
- Filter for partial demineralization PNC 864017
- Kit to measure total and partial water hardness PNC 864050
- Rinse booster pump kit for single tank pressure dishwasher PNC 864051
- Cutlery container - yellow PNC 864242
- Filter for total demineralization PNC 864367

APPROVAL: _____

**Warewashing
Small Glasswasher, double skin with drain pump and detergent
dispenser-UK plug, 30r/h**

- Pressure reducer for single tank dishwasher PNC 864461
- Kit 4 plastic boxes for cutlery - yellow PNC 865574
- Cover rack for small and light items (500x500 baskets) PNC 867016
- BASKET FOR GLASSES-395X395X115 MM PNC 867033
- Basket for 16 plates diam.190 mm, 8 plates diam. 240 mm PNC 867052
- Basket for glasses (h 100 mm) PNC 867053
- Basket for glasses (h 200 mm) PNC 867054
- Basket for glasses and saucers/cutlery inserts PNC 867055
- Basket for glasses with angled base PNC 867056
- Round basket kit with square frame PNC 867057
- Insert for "flute" glasses PNC 867058
- Insert for 14 saucers PNC 867060
- Inclined insert for cups PNC 867061
- Insert for 7 plates d. 240mm PNC 867062
- Square basket with angles for glasses 400x400x150 PNC 867067



Electric

Supply voltage:	
402168 (VGWSIGUK)	230 V/1N ph/50 Hz
Total Watts:	2.3 kW
Boiler heating elements:	2 kW
Tank heating elements:	0.8 kW
Wash pump size:	0.3 kW

Water:

Pressure, bar min/max:	1.8-3 bar
Water supply temperature*:	10 °C
Drain line size:	27mm
Boiler Capacity (lt):	5
Incoming water line size:	G 3/4"
Washing cycle temperature:	55-65 °C
Washing tank capacity (lt):	6
Hot rinse cycle temperature:	80-90 °C
Hot rinse cycle water consumption (lt):	2.3

Key Information:

Baskets per hour*:	30
N° of working cycles - sec.:	1 (120)
Cell dimensions - width:	400 mm
Cell dimensions - depth:	400 mm
Cell dimensions - height:	290 mm
External dimensions, Height:	715 mm
External dimensions, Width:	460 mm
External dimensions, Depth:	565 mm
Net weight:	37 kg
Shipping weight:	42 kg
Shipping height:	900 mm
Shipping width:	500 mm
Shipping depth:	620 mm
Shipping volume:	0.28 m³
Noise level:	67.5 dBA