



Warewashing Small Single Skin Glasswasher, drain pump and rinse aid dispenser,30r/h

ITEM # _____
MODEL # _____
NAME # _____
SIS # _____
AIA # _____



402300 (VSP)

Glasswasher (small), with
single skin, drain pump and
rinse aid dispenser, 1 cycle,
30r/h

Short Form Specification

Item No.

Unit shall be Glasswasher type hot water rinsing using rack dimension of 400*400mm. Electrical characteristics to be 230 volts single phase 50Hz operation with one wash cycle of 120 seconds. Washing performance is ensured by a powerful wash pump, revolving washing spray arms from both bottom and top. Rinse temperature and pressure guaranteed by built in pressure boiler. Double skinned counter-balance door. Large door opening of 290mm for washing tall glasses. Single skinned cabinet. Pressed tank with round corners. 304 stainless steel construction to include door, frame, wash arms and rinse arms. The unit shall include drain pump, detergent and rinse aid dispenser pumps and is equipped with electric cable with Schuko plug.

Main Features

- Built-in rinse aid dispenser with automatic initial and continuous cycle loading for perfect result while minimizing service and maintenance needs.
- Deep drawn pressed wash tank with fully rounded corners, sloped towards the drain to prevent dirt build up provides fast drainage in only a few minutes. Pressed wash tank with no welded points offer a guaranteed water tight solution.
- 120 seconds cycle.
- Built-in pressure boiler designed to raise incoming water to a guaranteed minimum temperature of 82°C for sanitizing rinse. No external boiler is required.
- Maximum capacity of 30 racks per hour.
- Simple operation control panel.
- Equipped with single phase electrical cable and Schuko plug for easy and fast installation.
- Easy service access to main components without moving the unit.
- Washing system endowed with rotating washing arms, high powered wash pump and large capacity wash tank for professional washing.
- Equipped with drain pump for easy and quick installation without opening the machine.

Construction

- Completely closed on the back by a cover plate.
- Unit to feature rinse aid dispenser pump.
- Internal components (arms and filter) are easy extractable.
- Insulated double skin door construction preserves heat inside the tank to lower energy consumption and the noise. Counter-balance mechanism minimizes impact when opening and closing.
- Finished in top quality materials to ensure durability.
- Robust structure thanks to stainless steel construction.

Included Accessories

- 1 of Square basket for glasses 400x400x150mm PNC 864470
- 1 of Insert for 12 saucers, 290x90x75mm PNC 867048
- 1 of Square cutlery container, 89x113x113mm PNC 867049

Optional Accessories

- Square basket for glasses, 400x400x1100mm ☐ PNC 867039
- Round basket for glasses, 400x180mm ☐ PNC 867047
- Inclination for glasses 400x400mm ☐ PNC 867069
- KIT DETERGENT DISPENSER FOR SINGLE SKIN XS & S GLASSWASHER ☐ PNC 867072

APPROVAL: _____

Warewashing
Small Single Skin Glasswasher, drain pump and rinse aid
dispenser,30r/h

Electric

Supply voltage:	220-240 V/1 ph/50 Hz
402300 (VSP)	
Default Installed Power:	2.7 kW
Boiler heating elements:	2.5 kW
Tank heating elements:	2 kW
Wash pump size:	0.2 kW

Water:

Pressure, bar min/max:	2-5 bar
Water supply temperature*:	10-65 °C
Drain line size:	29mm
Washing tank capacity (lt):	16
Water consumption per cycle (lt):	2
Boiler Capacity (lt):	2.5
Incoming water line size:	3/4"

Key Information:

Baskets per hour*:	30
Working cycles time (sec.):	120
Wash temperature:	60°C
Rinse temperature:	82 °C
Cell dimensions - width:	400 mm
Cell dimensions - depth:	400 mm
Cell dimensions - height:	290 mm
External dimensions, Width:	455 mm
External dimensions, Height:	700 mm
External dimensions, Depth:	550 mm
Net weight:	37.5 kg
Shipping weight:	41.5 kg
Shipping height:	850 mm
Shipping width:	540 mm
Shipping depth:	630 mm
Shipping volume:	0.31 m³
Noise level:	61 dBA